



2390 LED

LED projector

- Multilumen and Multicolour
- Universal mounting bracket
- Sensor accessories

The 2390 G2 LED is a spotlight for illuminating outdoor areas such as construction sites, docks and shipyards, storage areas and container yards as well as for accent lighting and illuminating buildings. Thanks to Multilumen and Multicolour, a total of 8 lumen packages in 2 light colours each are available with just 3 luminaires. Suitable for all mounting situations thanks to universal mounting brackets. This way you will master the job!

Why you'll master the job with the 2390 G2 LED floodlight

- Flexible adjustment of luminaire luminous flux and light colour thanks to Multilumen and Multicolour
- Sensor available as an accessory
- Swivel mounting bracket for suspended and upright installation
- 0.8 m connection cable
- Efficient illumination of large areas thanks to lens optics with asymmetrical medium-wide light distribution characteristics
- Efficiency: up to 150 lm/W
- Reliable service life (50,000 h, L80)

2390 LED at a glance

| | |
|--|---|
| Dimensions | 241 x 309 x 48 mm, 361 x 399 x 59 mm, 419 x 449 x 61 mm |
| Luminaire luminous flux | Multilumen: 2.000 / 3.000 / 5.000 lm, 8.000 / 10.000 / 15.000 lm, 15.000 / 20.000 / 25.000 lm |
| Colour Temperature | Multicolour: 3.000 K / 4.000 K |
| Protection rating, Safety class | IP65 / IK08, SK: I |
| Weight | 1,5 kg, 4,2 kg, 5,7 kg |
| Service life | 50.000 h (L80) |

All versions of 2390 G2 LED

| product reference | TOC | Luminous flux [lm] | Wattage [W] | Light colour [K] | Dimensions LxWxH [mm] | Replacement W |
|---|---------|--------------------------|----------------|------------------|-----------------------|---------------|
| 2390 G2 AM9L 20/30/50/ML-8MC 1G1W ET | 8420740 | 2.000 / 3.000 / 5.000 | 14 / 22 / 40 | 4.000 / 3.000 | 241 x 309 x 48 | HQI-TS 70W |
| 2390 G2 AM9L 150/200/250/ML-8MC 1G1W ET | 8420940 | 15.000 / 20.000 / 25.000 | 90 / 126 / 160 | 4.000 / 3.000 | 419 x 449 x 61 | HQI-TS 250W |
| 2390 G2 AM9L 80/100/150/ML-8MC 1G1W ET | 8420840 | 8.000 / 10.000 / 15.000 | 56 / 73 / 120 | 4.000 / 3.000 | 361 x 399 x 59 | HQI-TS 150W |

Accessories 2390 G2 LED

| product reference | TOC | Description | Dimensions LxWxH [mm] | Weight (kg) |
|-------------------|---------|-----------------------------------|-----------------------|-------------|
| 2390 HF SENSOR | 7641200 | Motion sensor / brightness sensor | 70 x 35 x 100 | 0,1 |

All technical data as well as weight details and dimensions are carefully created. Errors are not excluded. Product pictures are an example and may differ from the original. We reserve the right to make changes that serve progress.